BS8.00Offshore

Euro Offshore Services' achievements on the water would not have been possible without an on-going extensive program of design, manufacturing and process assessment throughout our manufacturing plant. The factory has expanded into the RIB market using our extensive knowledge gained in 15 years of building and designing for, high demanding, professional customers.

Using our specialist in house Technical and Design team, each craft is carefully researched and designed to produce exceptional on-the-water performance with hull design, tube geometry, shape, carrying capacity and operational characteristics all giving our range of craft outstanding handling, buoyancy, seaworthiness, stability and safety.

Construction:
Hull & Deck.

5 Year non-prorated structural hull warranty. Hand laid-up vinyl ester-fibreglass hull.
Variable dead rise deep V-hull.
Non-skid decks.

Self bailing decks.

Tube & Valves.
HD 1600 DTEX Neoprene-Hypalon® Tube.
Hand glued pressure tested tube.
UV and fuel-chemical resistance Hypalon®.
6 Pressurized compartments.
6 Pcs. "flush" mounted overpressure valve's.
6 Pcs. "flush" mounted inflation valve's.
10 HD NON –skid rubber patches on the tube.
Double HD protection fenders.
Inner & Outer grip line's.

Options:
- Professional electrical installation acc. IP67.
- T-Top Aluminium.
- A-frame Aluminium.
- Extra fuel tanks Stainless Steel 316.
- Transom boarding platform Aluminium.
- Backrest with collapsible seat aluminium.
- Jockey and console layout according client specifications.
- Single or twin inboard Diesel installations.
- Single, twin or Triple outboards.
- Semi automatic bilge pump.
- Emergency manual operated bilge pump.e outboard conf.

Specifications:
Length 8.25m
Beam 3.0m
Draft 0.5m
Boat Weight without engine 3.086lbs/1400kg.
Weight capacity 4,000lbs/1814kg.
Person capacity 16
Fuel capacity 93 gal./351L.
Transom height STD
Max Hp. 600
Dead rise @ Transom 24°
Classification ABYS/CE
-A ocean

Standard Equipment:
- 316 Stainless steel deck hardware.
- Stainless steel towing eye's(2) and bow eye.
- Heavy duty marine grade aluminium bow hatch.
- Stainless steel lifting eye's. (4)
- Bow towing device with fuel inlet.
- Stainless steel fuel tank.
- Aluminium grip bars. (6)
- Stainless steel transom U-plate.

Euro Offshore Services.nl

Euro Offshore Services B.V.
Ferrandstraat 4
4251 LL WERKENDAM
Phone : +31 183 500765
Fax : +31 183 691019
E-mail : info@eurooffshoreservices.nl
Web-site: www.eurooffshoreservices.nl